

AMATEUR • SWL SHORTWAVE • SPECTRUM • SPECIALTY

only hallicrafters...

offers precision-engineered radio receivers,
transmitters and two-way transceivers covering every known professional
and entertainment broadcasting frequency in the world.



YOU'RE IN THE GLOBAL COMMUNICATIONS COMMUNITY WITH A HALLICRAFTERS








the hallicrafters co.
A Subsidiary of Northrop Corporation



600 Hicks Road, Rolling Meadows, Illinois 60008 U.S.A.
Phone: 312-259-9600
TWX: 910-687-3785
Telex: 25-3707 • Cable: Hallicraft











AMATEUR EQUIPMENT & ACCESSORIES

MODEL	Shp'g Wt.	DESCRIPTION	Net
 SR-2000	30 lbs.	"Hurricane" 2000 W. P.E.P. 80-10M SSB/CW Transceiver. Our most powerful, compact system features built-in noise blanker, Vox, AALC, RIT, calibrator. 1 kHz readout, CW sidetone, 1 uv sensitivity for 20 db SN/N+N in industry's smallest package configuration.	\$1195.00
 P-2000-AC	65 lbs.	Solid-state matching power supply console for "Hurricane." Features 3" x 5" voice frequency speaker, two meters for P.A. plate current and voltage. 115/230 VAC, 50/60 Hz.	450.00
 SR-400	26 lbs.	CYCLONE II 400 W. P.E.P. (with 3rd order distortion products 30 db down) 80-10M SSB/CW Transceiver. Cleanest signal on the air with Hallicrafters latest, field-proven fixed/mobile unit features built-in RIT, AALC, Notch and CW filters, noise blanker, VOX . . . over a score of Ham-tested features for SSB and CW operation in any operating mode.	895.00
 PS-500A-AC	28½ lbs.	Solid-state matching power supply console for CYCLONE II. Features 3" x 5" voice frequency speaker for both 115/230 VAC, 50/60 Hz.	129.95
P-500 DC	10 lbs.	Solid-state ruggedized power supply for CYCLONE II mobile or other 11-16 VDC negative ground installations. Does not have built-in speaker.	159.95
MR-400	13 lbs.	Universal heavy-duty slide-in mobile mounting rack for CYCLONE II.	89.95
 HA-20	11 lbs.	"Dual Receive" DX adaptor. Remote VFO/VSWR console for Hurricane and Cyclone transceivers. Stable 1 kHz VFO with expanded scale VSWR meter completely self-powered. Unmatched operating capability available only from Hallicrafters.	199.95
 HA-18A	1 lb.	Learn code the easy way with Hallicrafters transistorized code practice oscillator with variable pitch control and earphone provision. Includes oscillator, code practice key and batteries. Contact American Radio Relay League (ARRL), Newington, Connecticut, 06111, for booklets on "How to Become a Radio Amateur."	9.95
HA-19	1 lb.	Plug-in 100kHz crystal calibrator for SX-122A or SX-133.	39.95
 HA-1A	9 lbs.	Hallicrafters famous "T.O. Keyer" new and improved "Stradivarius of electronic Keyers" with digital circuitry for perfect CW sidetone features constant ratio timing, self-completing dots and dashes, vacuum sealed, mercury wetted relay used to key transmitter, adjustable speed 10 to 65 WPM.	119.95

SHORTWAVE RECEIVERS

MODEL	Shp'g Wt.	DESCRIPTION	Net
 <p>SX-122A</p>	32 lbs.	Hallicrafters best professional type AM/CW/SSB communications receiver with dual conversion through 535kHz to 34 MHz covers 83 shortwave services plus standard AM broadcast. Product detector. Noise limiter. Uses HA-19 crystal calibrator. Requires external speaker. Dimensions: (WHD) 19" x 8" x 10". Weight 29 lbs.	\$550.00
 <p>SX-133</p>	35 lbs.	Our newest communications type AM/CW/SSB high-performance receiver with crystal filter, product detector. Covers 81 shortwave services plus standard AM broadcast 535kHz to 31.5MHz. Bandspread calibrated for four popular shortwave bands and five amateur bands. Includes S-meter, NL, antenna trimmer and selectivity controls. Uses HA-19 crystal calibrator. Requires external speaker. Dimensions: (WHD) 18 $\frac{3}{4}$ " x 8" x 10 $\frac{1}{4}$ ".	350.00
 <p>S-240</p>	11 lbs.	Hallicrafters' best all solid-state AM/FM/SW/SSB entertainment type receiver with built-in speaker and SW antenna. Covers 76 shortwave services from 2 to 30 MHz plus standard AM and FM broadcast. Transformer operated with BFO, tuning meter, fine tune, AFC and over 1000 milliwatts audio output. Tuner output jack for Hi-Fi use. Provision for external speaker or headphones. Walnut grained vinyl-clad steel cabinet with diecast front. Dimensions: (WHD) 13 $\frac{7}{8}$ " x 5 $\frac{7}{8}$ " x 8". Weight: 10 $\frac{1}{2}$ lbs. 105-125 V.A.C.	119.95
 <p>S-214</p>	11 lbs.	Our finest all solid-state AM/FM and international SW broadcast entertainment type receiver. Designed specifically for the shortwave broadcast enthusiast, the S-214 covers four easy-to-tune popular 49M, 31M, 21M, and 19M international broadcast bands plus standard AM and FM broadcast. Transformer operated with slide rule dial, tone, AFC and over 1000 milliwatts of audio output. Tuner output jack for hi-fi use. Built-in SW antenna and speaker. Black vinyl clad steel cabinet with diecast front. Dimensions: (WHD) 13 $\frac{7}{8}$ " x 5 $\frac{7}{8}$ " x 8". Weight: 10 lbs. 105-125 V.A.C.	109.95
 <p>S-120A</p>	8 lbs.	Hallicrafters' most popular general coverage all solid-state STARQUEST AM/SW receiver with built-in speaker. Covers 76 shortwave services from 1.7 to 30MHz plus standard AM broadcast. Will operate AC or off of 12v battery power for emergency use. Includes BFO, bandspread, calibrated slide-rule dial, phone jack. Dimensions: (WHD) 12" x 5 $\frac{1}{4}$ " x 5".	79.95
 <p>CR-44A</p>	8 lbs.	Hallicrafters' best 5-band direction-finder portable receiver with direct readout azimuth indicator and null meter for entertainment, safety and navigation. Covers standard AM and FM broadcast, long wave navigation (185-400 kHz), marine and shortwave (2-5.2 MHz), and public safety, weather, police and fire (152-174 MHz). Full direction finder capability, two meters, dial light, tone, sensitivity dual antennas, large 4" speaker. Requires 4 "D" cells or optional AC supply. Dimensions: (WHD) 11 $\frac{1}{2}$ " x 9" x 3 $\frac{3}{4}$ ".	149.95

SPECIALTY

MODEL	Shp'g Wt.	DESCRIPTION	Net
 CRX-106	1 lb.	"Portamon" Tuneable 27-50 MHz portable monitor receiver. Fully transistorized. RF stage. Noise limiter. Squelch control. Operates on 9 volt battery. Die cast front. Provision for external antenna, earphone, and AC adapter. With carry strap. Dimensions: (WHD) 2 $\frac{3}{4}$ " x 6" x 1 $\frac{5}{8}$ ".	\$39.95
CRX-101	1 lb.	"Portamon" Tuneable 108-135 MHz. Same physical specifications as above (less squelch).	39.95
CRX-107	1 lb.	"Portamon" Tuneable 144-174 MHz. Same physical specifications as CRX 106.	39.95
 CRX-103A	4 $\frac{1}{2}$ lbs.	Civic patrol Tuneable 30-50 MHz table model monitor receiver. Fully transistorized. RF stage. Squelch control, full 1000 milliwatt audio stage. Large 4 x 6 inch front mounted speaker. Built in 117 V.A.C. power supply. Provision for an external antenna. Dimensions: (WHD) 13 $\frac{1}{8}$ " x 5 $\frac{1}{2}$ " x 3 $\frac{1}{2}$ ".	59.95
CRX-104	4 $\frac{1}{2}$ lbs.	Civic patrol Tuneable 108-135 MHz.	49.95
CRX-105A		Civic patrol Tuneable 152-174 MHz.	59.95
 R-47	3 lbs.	4" Speaker for SX-130, SX-122, SX-146 . . . for voice frequencies only . . . 3.2 ohm voice coil. Dimensions: (WHD) 5 $\frac{1}{4}$ " x 5 $\frac{1}{2}$ " x 3 $\frac{1}{2}$ ".	19.95
 R-49	4 lbs.	Mobile speaker 3.2 ohm voice coil moisture proof cone. Dimensions: (WHD) 5 $\frac{1}{4}$ " x 5 $\frac{1}{2}$ " x 3 $\frac{1}{2}$ " plus bracket.	17.95
 R-50	8 lbs.	Highly efficient oval 5" x 7" speaker matching in styling the SX-130. 3.2 ohm voice coil handles up to 5 watts of program material. Can be used with any 3.2 ohm receiver. Dimensions: (WHD) 8 $\frac{1}{4}$ " x 8 $\frac{3}{8}$ " x 8 $\frac{7}{8}$ ". Weight: 6 $\frac{1}{2}$ lbs.	39.95
 R-51	8 $\frac{1}{2}$ lbs.	Same as R-50 except has 4" x 6" oval speaker and attractive clock built into it. Dimensions: Same as R-50. Weight: 7 lbs.	49.95
 RA-48	1 lb.	Professional type communications headphones. Universal impedance.	29.95
HA-36	1 lb.	6 V.D.C. adaptor for operation of CR 44A from 110 V. 60 cycle A.C.	12.50
HA-39	1 lb.	9 V.D.C. adaptor for operation of CRX 101, 106 or 107 from 110 V. 60 cycle A.C.	7.50
 TIME DIAL		WORLD TIME DIAL AND FREQUENCY CHART Circular slide chart converts local time to Greenwich Mean Time (GMT) or displays local time in any other 23 zones around the world. Frequency Chart on reverse side lists major broadcasting, communications, and emergency radio services presently in use around the world.	1.00

Printed in U.S.A.
S-816E

the hallicrafters co.
A Subsidiary of Northrop Corporation



600 Hicks Road, Rolling Meadows, Illinois 60008 U.S.A.
Phone: 312-259-9600
TWX: 910-687-3785
Telex: 25-3707 • Cable: Hallicraft